

RoughDeck™ HP-H Heavy Capacity Floor Scale



Approvals



Standard Features

- Four NTEP - certified alloy steel, welded seal, shear beam load cells
- Unique side-entry "integral" aluminum J-box with quick disconnect
- All-inclusive **5-YEAR** limited warranty
- Rugged diamond safety treadplate deck
- Rigid structural steel channel frame
- Four adjustable stainless steel SUREFOOT support feet
- Threaded eyebolt holes for easy lifting

Specifications

APPROVALS:

NTEP - certified, CC# 92-001A9
Class III, 5000d,

END LOAD CAPACITY:

100% full scale at 20,000 lbs
66% full scale at 30,000 lbs

mV/V OUTPUT:

1.50-1.87
mV/V nominal

CABLE LENGTH:

20 ft (6.1 m) (for connecting J-box to indicator)

WARRANTY:

5-year limited warranty

BASES

PART # w/Quick Connector	PART # w/Out Quick Connector	SIZE (W X L X H)	CAPACITY	EST. SHIP WT
66474	67717	4' x 4' x 4"	20,000 lb (9,071.85 kg)	601 lb
66475	67718	4' x 5' x 4"	20,000 lb (9,071.85 kg)	775 lb
66476	67719	4' x 6' x 4"	20,000 lb (9,071.85 kg)	926 lb
66477	67720	4' x 7' x 4"	20,000 lb (9,071.85 kg)	1135 lb
66478	67721	5' x 5' x 4"	20,000 lb (9,071.85 kg)	926 lb
66479	67722	5' x 6' x 4"	20,000 lb (9,071.85 kg)	1104 lb
66480	67723	5' x 7' x 4"	20,000 lb (9,071.85 kg)	1377 lb
66481	67724	6' x 6' x 4"	20,000 lb (9,071.85 kg)	1319 lb
66482	67725	6' x 8' x 4"	20,000 lb (9,071.85 kg)	1861 lb
66483	67726	7' x 9' x 4"	20,000 lb (9,071.85 kg)	2408 lb
66484	67727	7' x 10' x 4"	20,000 lb (9,071.85 kg)	2959 lb
66485	67728	8' x 10' x 4"	20,000 lb (9,071.85 kg)	3108 lb
66486	67729	4' x 4' x 5"	30,000 lb (13,607.77 kg)	675 lb
66487	67730	4' x 5' x 5"	30,000 lb (13,607.77 kg)	839 lb
66488	67731	4' x 6' x 5"	30,000 lb (13,607.77 kg)	1071 lb
66489	67732	4' x 7' x 5"	30,000 lb (13,607.77 kg)	1200 lb
66490	67733	5' x 5' x 5"	30,000 lb (13,607.77 kg)	1021 lb
66491	67734	5' x 7' x 5"	30,000 lb (13,607.77 kg)	1448 lb
66492	67735	6' x 6' x 5"	30,000 lb (13,607.77 kg)	1438 lb
66493	67736	7' x 10' x 5"	30,000 lb (13,607.77 kg)	3372 lb
66494	67737	8' x 10' x 5"	30,000 lb (13,607.77 kg)	3699 lb