

EPSON TM-U295 Ticket Printer



Standard Features

- High-speed 1.9 to 2.3 lines per second printing
- Single copy or up to four-part multicopy ticket printing
- Functions in slave capacity, printing information sent via RS-232

Approvals



Specifications

PRINT SPEED:

1.9 to 2.3 lines per second (5 x 7 character, 3 dot line spacing)

COLUMN CAPACITY:

35/42 columns

CHARACTERS PER LINE:

35 standard font

PRINT AREA:

2.59" W (65.8 mm W)

CHARACTER FORMATION:

5 x 7 and 7 x 7 dot matrix

CHARACTER HEIGHT:

0.11 standard font

CHARACTER SET:

Full 96-character ASCII; with software control - 32 international characters, 128 x 2 graphic characters;

LINE SPACING:

0.16" (4.06 mm) software programmable in 1/60" units

PRINTHEAD LIFE:

Approximately 100,000,000 strokes/pin

FORM THICKNESS:

Single-ply - 0.003" to 0.009" (0.08 to 0.23 mm)
Copy paper - 0.003" to 0.014" (0.08 to 0.36 mm)

RIBBON:

Cassette-type purple ribbon. Ribbon life is approximately 1.5 million characters (continuous prints). Black ink also available.

SERIAL INTERFACES:

RS-232 compatible (25-pin D-subconnector)

BAUD RATES:

1200, 2400, 4800, 9600, selectable

PARITY:

7 or 8 bits, none, even or odd

STOP BITS:

1 or more

HANDSHAKING:

DTR/DSR or XON/XOFF control selectable

OVERALL DIMENSIONS:

7.08" W x 7.49" D x 3.99" H
(180 mm W x 190.5 mm D x 101.5 mm H)

APPROVALS:

UL listed, CSA certified, CE marked

WARRANTY:

1-year limited warranty (includes printhead)